

Figure 1




Figure 2





Figure 3



Formula (1)

Figure 4

$R_1$	$R_2$	$R_3$ H : vinylbenzyl (molar ratio)	n
methyl	benzyl	0:100	3
methyl	benzyl	5:95	3
methyl	benzyl	60:40	3
methyl	benzyl	40:60	3
methyl	benzyl	20:80	3

Figure 5

	Additive	Addition amount (wt%)	Annealing (°C)	Dielectric properties (at 2 GHz)		Insulation resistance	Remarks
				$\epsilon$	Q		
Example 1	MnCO <sub>3</sub>	0.15	1000	10.71	304	5.5 × 10 <sup>13</sup>	Added to/mixed with finely milled powder
Comparative Example 1	Bi <sub>2</sub> O <sub>3</sub>	1.0	1000	14.43	290	4.5 × 10 <sup>11</sup>	Added to/mixed with finely milled powder
Comparative Example 2	SiO <sub>2</sub>	1.0	1000	11.36	335	2.9 × 10 <sup>11</sup>	Added to/mixed with finely milled powder
Comparative Example 3	CaCO <sub>3</sub>	1.0	1000	11.85	270	2.0 × 10 <sup>11</sup>	Added to/mixed with finely milled powder
Comparative Example 4	None	—	1000	9.33	312	3.1 × 10 <sup>10</sup>	—

Figure 6

	Additive	Addition amount (wt%)	Annealing (°C)	Dielectric properties (at 2 GHz)		Insulation resistance	Remarks
				$\epsilon$	Q		
Example 2	MnCO <sub>3</sub>	0.15	1100	12.10	355	$9.9 \times 10^{13}$	Added to/mixed with finely milled powder
Example 1	MnCO <sub>3</sub>	0.15	1000	10.71	304	$5.5 \times 10^{13}$	Added to/mixed with finely milled powder
Comparative Example 5	Bi <sub>2</sub> O <sub>3</sub>	1.0	1100	13.17	368	$2.6 \times 10^{11}$	Added to/mixed with finely milled powder
Comparative Example 1	Bi <sub>2</sub> O <sub>3</sub>	1.0	1000	14.43	290	$4.5 \times 10^{11}$	Added to/mixed with finely milled powder
Comparative Example 6	SiO <sub>2</sub>	1.0	1100	10.80	365	$1.4 \times 10^{12}$	Added to/mixed with finely milled powder
Comparative Example 2	SiO <sub>2</sub>	1.0	1000	11.36	335	$2.9 \times 10^{11}$	Added to/mixed with finely milled powder
Comparative Example 7	CaCO <sub>3</sub>	1.0	1100	11.92	310	$1.4 \times 10^{11}$	Added to/mixed with finely milled powder
Comparative Example 3	CaCO <sub>3</sub>	1.0	1000	11.85	270	$2.0 \times 10^{11}$	Added to/mixed with finely milled powder
Comparative Example 8	None	—	1100	11.58	359	$2.6 \times 10^{10}$	—
Comparative Example 4	None	—	1000	9.33	312	$3.1 \times 10^{10}$	—

Figure 7




Figure 8A




Figure 8B






Figure 9A




Figure 9B




Figure 9C




Figure 10A





Figure 10B



10/535477

Figure 11

Additive	Addition amount (wt%)	Annealing (°C)	Dielectric properties (at 2 GHz)		Insulation resistance	Remarks
			$\epsilon$	Q		
MnCO <sub>3</sub>	0.05	1100	11.73	354	$2.7 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.10	1100	11.44	351	$3.4 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.15	1100	12.10	355	$9.9 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.20	1100	11.47	352	$4.6 \times 10^{13}$	Added to/mixed with finely milled powder

10/535477

Figure 12

Additive	Addition amount (wt%)	Annealing (°C)	Dielectric properties (at 2 GHz)		Insulation resistance	Remarks
			$\epsilon$	Q		
MnCO <sub>3</sub>	0.05	1150	12.18	363	$2.6 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.10	1150	12.07	359	$2.2 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.15	1150	12.21	358	$3.3 \times 10^{13}$	Added to/mixed with finely milled powder
MnCO <sub>3</sub>	0.20	1150	11.64	347	$2.4 \times 10^{13}$	Added to/mixed with finely milled powder

10/535477

Figure 13

	Composition (wt%)					Additive (wt%)	Powder type	Sphe-ricity	Specific surface area (m <sup>2</sup> /g)	Electric resistivity (Ω·cm)	Remarks
	BaO	Nd <sub>2</sub> O <sub>3</sub>	TiO <sub>2</sub>	Bi <sub>2</sub> O <sub>3</sub>	MnO						
1	18.93	41.19	39.88	—	—	—	Spherical powder	0.97	0.459	7.7 × 10 <sup>10</sup>	Without MnO in final composition
2	18.93	41.19	39.88	—	—	—	Spherical powder	0.98	3.436	5.1 × 10 <sup>10</sup>	Without MnO in final composition
3	18.93	41.19	39.88	—	—	—	Spherical powder	0.85	2.688	1.0 × 10 <sup>11</sup>	Without MnO in final composition
4	16.6	38.86	41.7	—	—	—	Spherical powder	0.92	3.097	6.1 × 10 <sup>12</sup>	Without MnO in final composition
5	18.93	41.19	39.88	—	—	—	Spherical powder	0.88	1.824	5.8 × 10 <sup>9</sup>	Without MnO in final composition
6	18.93	41.19	39.88	—	—	—	Spherical powder	0.99	1.702	5.3 × 10 <sup>10</sup>	Without MnO in final composition
7	18.93	41.19	39.88	—	—	—	Spherical powder	0.92	2.097	6.1 × 10 <sup>10</sup>	Without MnO in final composition
8	18.93	41.19	39.88	—	—	—	Spherical powder	0.83	1.570	1.1 × 10 <sup>11</sup>	Without MnO in final composition
9	18.93	41.19	39.88	—	—	—	Spherical powder	0.81	2.235	3.1 × 10 <sup>11</sup>	Without MnO in final composition
10	18.93	41.19	39.88	—	—	—	Spherical powder	0.96	2.092	2.0 × 10 <sup>11</sup>	Without MnO in final composition
11	18.93	41.19	39.88	—	—	—	Crushed powder	0.72	1.600	4.3 × 10 <sup>13</sup>	Without MnO in final composition
12	18.93	41.19	39.88	—	—	—	Crushed powder	0.63	1.819	3.1 × 10 <sup>13</sup>	Without MnO in final composition
13	18.93	41.19	39.88	—	—	—	Spherical powder	0.94	0.465	2.6 × 10 <sup>10</sup>	Without MnO in final composition
14	18.93	41.19	39.88	—	—	Bi <sub>2</sub> O <sub>3</sub> 0.15	Spherical powder	0.87	0.798	2.6 × 10 <sup>11</sup>	Without MnO in final composition
15	16.6	38.86	41.7	2.751	0.088	—	Crushed powder	0.61	1.617	4.7 × 10 <sup>13</sup>	With MnO in final composition
16	16.6	38.86	41.7	2.751	0.088	—	Spherical powder	0.83	0.426	4.5 × 10 <sup>13</sup>	With MnO in final composition
17	18.93	41.19	39.88	—	—	MnCO <sub>3</sub> 0.15	Spherical powder	0.90	0.454	9.9 × 10 <sup>13</sup>	With MnO in final composition

Figure 14




Figure 15A  
Crushed powder




Figure 15B  
Spherical powder




Figure 16

Annealing (°C)	Dielectric properties (at 2 GHz)		Insulation resistance	Remarks
	$\epsilon$	Q	Electric resistivity ( $\Omega \cdot \text{cm}$ )	
1000	11.76	359	$4.5 \times 10^{13}$	MnCO <sub>3</sub> added when mixing